



Gollmer & Hummel are a fifth generation business pioneering hose products in Germany for almost 150 years

For more information:

please contact Michael 087 9008899 or Noel 087 9892998

[info@hpmpfire.ie](mailto:info@hpmpfire.ie)

Dublin Road, Tullow, Co Carlow R93 XY24

[www.hpmpfire.ie](http://www.hpmpfire.ie)

## Lay Flat Delivery Hoses - Progress

HPMP Fire have teamed up with Gollmer & Hummel to bring you one of the most resistant lay flat hoses on the market, designed for use in tough conditions.



### Progress Hoses are:

- Lightweight and highly flexible
- Excellent resistance to ageing and ozone
- Extremely resistant to seawater and a wide range of chemicals (hose lining)
- Mildew and rot proof
- Very easy to repair
- Stainless Steel wire binding is standard on all hoseguards – These hoseguards perfectly shields heavily loaded tail pieces. Made from 4mm thick, high grade EPDM rubber, it guards against the heaviest of loads and offers long-term resistant to all types of foaming agents as well as a wide range of acids and alkalis.

Progress Hose Specification	
Standard length:	15,18,20,23,30m
Bore Size (mm):	25, 38, 40, 42, 45, 52, 55, 64, 70, 75, 89,
Hose Test Pressure:	Maintained for 1 min, in accordance with DIN 14811: Ø 25-75: 24 bar  Maintained for 1 min, in accordance with BS 6391: 2009 Ø 38-89: 22.5 bar
Working Pressure:	DIN 14811 with STORZ couplings: Ø 25-75mm: max. working pressure 16 bar  BS6391:2009 with British Instantaneous Couplings Ø 38-76 mm: max working pressure 15 bar Ø 89: max. working pressure 12 bar
Temperature:	Continuous use - 20°C to + 80 ° C (water). Temporary up to +100 ° C (water)
Bespoke Options:	Single Lengths up to 200m Red as standard but colour according to customer specification



[www.gollmer-hummel.de](http://www.gollmer-hummel.de)

*Gollmer & Hummel are a fifth generation business pioneering hose products in Germany for almost 150 years.*